

QUADRO Q200



MAIN VERSIONS

WHITE 4000 °K
WHITE 3000 °K
8°
24°
36°

KEY FEATURES

- Modular
- Bright beam for long distance architectural applications
- 9 converging light beams with efficient hybrid lenses
- IP65, for outdoor use
- Die-cast aluminium resistant body
- Long lasting LED source, and maintenance savings
- Throw distance: 4-90 m

LIGHT SOURCE:

- Power engine: 9 x 20W White LED 4000 °K or 3000 °K
- Average led life: 50.000 Hours

SPECIFICATIONS:

Color

- White led

Beam angle

- 8°
- 24°
- 36°

Strobe/Dimmer

- Strobe: variable, random, pulse effects
- Dimmer: Linear digital 0-100% 16 bit resolution
- Flicker free, adjustable PWM frequency

Cooling

- Overheat protected

Mounting

- Adjustable mounting bracket
- Outdoor: IP65 protection

PHYSICAL SIZE:

- Attached drawings
- Weight: 7,5 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- RDM ready
- Bidirectional communication
- 3 Control channel modes: 1/3/6 channels
- 3 operational modes: DMX-512, Master/Slave, Auto
- Remote display function
- Upgradable software
- Display

AVAILABLE COLORS:

- Black
- Architectural grey
- Other on request


ELECTRICAL SPECIFICATION/ CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 150 W
- Power connection: free wire
- Dmx connection: free wire


ACCESSORIES:

- Free wire
- Optional parabola assembly
- Remote data information device
- Safety cord

- Accessories can be included in special offer



405



507

— 114 —