

# QUADRO 1000



## MAIN VERSIONS

**WHITE 3000 °K**  
**WHITE 4000 °K**  
**WHITE 5600 °K**  
**12° - 20°**  
**22° - 35°**  
**26°**

## KEY FEATURES

- Profile to shape the light beam, even, sharp and project gobo
- Bright beam for long distance architectural accent applications
- IP65, for outdoor use
- Extruded aluminium resistant body with plastic die-cast and silicon seals
- Throw distance: 4-60 m

## LIGHT SOURCE:

- Power engine: 200W White LED
- 3000/4000/5600 °K
- Average led life: 50.000 Hours

## SPECIFICATIONS:

### Color

- White led
- Color filters can be added internally

### Focus and zoom

- 3 different optical options:
- 12° - 20° linear zoom
- 22° - 35° linear zoom
- 26°

- focusable

### Framing shutters

- 4 framing adjustable internal shutters

### Gobo

- E size gobos

### Strobe/Dimmer

- Strobe: variable, random, pulse effects
- Dimmer: Linear digital 0-100% 16 bit resolution
- Flicker free, adjustable PWM frequency

### Cooling

- Overheat protected

### Mounting

- Adjustable mounting bracket
- Outdoor: IP65 protection

## PHYSICAL SIZE:

- Attached drawings
- Weight: 18 kg

## CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- RDM ready
- Bidirectional communication
- 3 Control channel modes: 1/3/6 channels
- 3 operational modes: DMX-512, Master/Slave, Auto
- Remote display function
- Upgradable software
- Display

## AVAILABLE COLORS:

- Black
- Architectural grey
- Other on request


## ELECTRICAL SPECIFICATION/ CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 180 W
- Power connection: free wire
- Dmx connection: free wire


## ACCESSORIES:

- Safety cord
- Remote data information device
- Gobo holder
- Metal, plastic, glass Gobos

- Accessories can be included in special offer



280



360

640