

# MODULO **SXT** PIXEL



## MAIN VERSIONS

**RGBW**  
**WHITE 3000°K**  
**8°**  
**25°**  
**45°**

## KEY FEATURES

- Individual pixel control, LED linear bar
- Versatile
- Energy efficient
- Light and bright
- Long lasting LED source, and maintenance savings
- Throw distance: 3-16 m

## LIGHT SOURCE:

- Power engine: 5 X 8W RGBW LED or 5 X 8W Warm White LED
- Average led life: 50.000 Hours

## SPECIFICATIONS:

### Color

- RGBW color mixing, linear adjustable color temperature
- Warm White 3000°K

### Beam angle

- 8°
- 25°
- 45°

### Strobe/Black-out/Dimmer

- Strobe: 1-25 flashes P/S or random strobe
- Dimmer: Linear digital 0-100%
- Flicker Free

### Pixel control

- Individual

### Cooling

- Overheat protected

### Mounting

- Adjustable mounting bracket

## PHYSICAL SIZE:

- Attached drawings
- Weight: 2,8 kg
- Packing dimension: 60x20x19 cm
- Gross weight: 3,8 kg

## CONTROL PROTOCOL

### AND PROGRAMMING:

- USITT Dmx 512/1990
- RGBW- 3 Control channel modes: 1/8/24 channels
- W- 3 Control channel modes: 1/4/9 channels
- 3 operational modes: DMX-512, Master/Slave, Auto
- LCD display

## AVAILABLE COLORS:

- Black
- Other on request

## ELECTRICAL SPECIFICATION/ CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 50 W
- Power connection: Powercon IN/OUT
- Dmx connection: 3-5 poles IN/OUT

## ACCESSORIES:

- Flight case
- C clamp
- Safety cord

- Accessories can be included in special offer

