

MODULO 100 PIXEL



MAIN VERSIONS

RGBW
WHITE 3000°K
WHITE 5600°K
11°
24°
36°

KEY FEATURES

- Modular
- A "Line-Array" of led lights
- Versatile, more Modulo 100 can be assembled together
- RGBW and white led fixture can be composed together, spread or converged
- Energy efficient
- Light and bright
- Long lasting LED source, and maintenance savings
- Throw distance: 3-24 m

LIGHT SOURCE:

- Power engine: 9 x 4 x 3W RGBW LED or 9 x 4 x 3W White LED
- Average led life: 50.000 Hours

SPECIFICATIONS:

Color

- RGBW color mixing, linear adjustable color temperature
- White 3000°K or 5600°K

Beam angle

- 11°
- 24°
- 36°

Strobe/Black-out/Dimmer

- Strobe: 1-25 flashes P/S or random strobe
- Dimmer: Linear digital 0-100%
- Flicker Free, adjustable PWM

Cooling

- Overheat protected, convective cooling

Mounting

- Adjustable mounting bracket

MODULARITY:

- 1X2
- 1X4
- 2X2
- more configuration available on request

PHYSICAL SIZE:

- Attached drawings
- Weight: 4,8 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- RDM ready
- Bidirectional communication
- RGBW- 3 Control channel modes: 4/8/12 channels
- W- 3 Control channel modes: 1/4/6 channels
- 3 operational modes: DMX-512, Master/Slave, Auto
- Remote display function
- Upgradable
- Display

AVAILABLE COLORS:

- Black
- Other on request


ELECTRICAL SPECIFICATION/ CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 60 W
- Power connection: Powercon IN/OUT
- Dmx connection: 3-5 poles IN/OUT


ACCESSORIES:

- Flight case
- C clamp
- Safety cord
- Remote data information device
- Modular brackets

- Accessories can be included in special offer



550



550

200