

MODULO **SXS**



MAIN VERSIONS

RGBW
WHITE 3000°K
8°
25°
45°

KEY FEATURES

- Individual pixel control, LED matrix panel and blinder
- Versatile
- Energy efficient
- Light and bright
- Long lasting LED source, and maintenance savings
- Throw distance: 3-16 m

LIGHT SOURCE:

- Power engine: 25 X 8W RGBW LED or 25 X 8W Warm White LED
- Average led life: 50.000 Hours

SPECIFICATIONS:

Color

- RGBW color mixing, linear adjustable color temperature
- Warm White 3000°K

Beam angle

- 8°
- 25°
- 45°

Strobe/Black-out/Dimmer

- Strobe: 1-25 flashes P/S or random strobe
- Dimmer: Linear digital 0-100%
- Flicker Free

Pixel control

- Individual

Cooling

- Overheat protected

Mounting

- Adjustable mounting bracket or Quick Lock

PHYSICAL SIZE:

- Attached drawings
- Weight: 10 kg
- Packing dimension: 61x61x21 cm
- Gross weight: 12 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- RGBW- 5 Control channel modes: 1/8/25/100/102 channels
- W- 3 Control channel modes: 1/10/25 channels
- 3 operational modes: DMX-512, Master/Slave, Auto
- LCD display

AVAILABLE COLORS:

- Black
- Other on request

ELECTRICAL SPECIFICATION/ CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 200 W
- Power connection: Powercon IN/OUT
- Dmx connection: 3 poles IN/OUT

ACCESSORIES:

- Flight case
- C clamp
- Safety cord
- Fly Bar
- Hanger
- Accessories can be included in special offer

