



1E500299

KEY FEATURES

- Bright beam moving head
- Effect engine
- Focus, rotating gobos and prism
- 3° beam angle
- Throw distance: 5-50 m

LIGHT SOURCE:

- Philips Platinum 5R
- Power: 189W
- CT: 7100° K
- Average led life: 2000 Hours

SPECIFICATIONS:

Movement

- Pan: 540°/630°optional (16 bit)
- Tilt: 265°(16 bit)
- Advanced 3 phases motor moving system: fast, stable and quiet
- X-Y repositioning

Color

- Color wheel: 12 dichroic filters
- +open, indexable, rainbow effect

Beam angle

- 3°

Gobo

- 1 Rotating gobo wheel:
- 8 interchangeable, indexable gobos
- + open
- Gobo shaking

Prism

- Rotating prism: 8 facets

Focus

- Motorized linear focus

Strobe/Black-out/Dimmer

- Strobe: variable, random, pulse effects
- Movement and wheel changing with black-out
- Dimmer: Linear digital 0-100%

Cooling

- Forced ventilation
- Controlled fan speed
- Temperature info

Mounting

- Any position
- Quick lock

PHYSICAL SIZE:

- Attached drawings
- Weight: 19 kg
- Packing dimension: 63x45.5x42.5 cm
- Gross weight: 21 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- Wireless ready
- 3 Control channel modes: 12/14/18 channels
- 4 operational modes: DMX-512, Slave, Auto, Audio
- LCD color display, auto lock
- Display settings via battery ready
- Hibernation
- Show editor
- Diagnostic system
- Software upgrade through DMX

AVAILABLE COLORS:

- Black
- Other on request


ELECTRICAL SPECIFICATION/ CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 350 W
- ON/OFF power switch
- Power connection: Powercon IN
- Dmx connection: 3-5 poles IN/OUT


ACCESSORIES:

- Powercon-Schuko power cord
- Dmx cable
- Safety cord
- C clamp
- Display battery
- Updater box
- Wireless
- Flight case

- Accessories can be included in special offer



376



496

308