

CLASSE **LS 200**



1E300499

KEY FEATURES

- LED spot moving head designed for most of standard venue
- As bright as majority of the lamp based 400/575 spots
- 16° beam angle
- Throw distance: 3-15 m
- Bright in both white and in colored beams
- Complete effect engine
- Focus

LIGHT SOURCE:

- Power: 180W COB LED
- CT: 6500°K
- Average led life: 50.000 Hours

SPECIFICATIONS:

Movement

- Pan: 540°/630° optional (16 bit)
- Tilt: 265° (16 bit)
- Advanced moving system: fast, stable and quiet
- X-Y repositioning

Color

- Color wheel: 8 dichroic filters + open, indexable, rainbow effect

Gobo

- 1 Static gobo wheel: 7 interchangeable gobos + open
- 1 Rotating gobo wheel: 7 interchangeable, indexable gobos + open
- Gobo shaking

Prism

- Rotating prism: 3 facets

Focus

- Motorized focus

Frost

- 0-100%

Iris

- Motorized Linear Iris 5%-100%

Strobe/Black-out/Dimmer

- Strobe: variable, random, pulse effects
- Movement and wheel changing with black-out
- Dimmer: 0-100%

Cooling

- Heat pipe combined with forced ventilation
- Controlled fan speed
- Temperature info

Mounting

- Any position
- Quick lock

PHYSICAL SIZE:

- Attached drawings
- Weight: 16 kg
- Packing dimension: 65x48.5x46.5 cm
- Gross weight: 18.5 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- Wireless ready
- 3 Control channel modes: 14/16/20 channels
- 4 operational modes: DMX-512, Slave, Auto, Audio
- Full color LCD display, auto lock
- Display settings via battery ready
- Hibernation
- Show editor
- Diagnostic system
- Software upgrade through DMX

AVAILABLE COLORS:


- Black
- Other on request

ELECTRICAL SPECIFICATION/ CONNECTIONS:


- AC input: 100-240V, 50/60HZ
- Max power consumption: 240 W
- ON/OFF power switch
- Power connection: Powercon IN/OUT
- Dmx connection: 3-5 poles IN/OUT

ACCESSORIES:

- Powercon-Schuko power cord
- Dmx cable
- Safety cord
- C clamp
- Display battery
- Updater box
- Wireless
- Flight case
- Accessories can be included in special offer



384



308

476