

DMX POWER SUPPLY



MAIN VERSIONS

500 mA
700 mA
1000 mA

KEY FEATURES

- Digital led power supply
- Master/Slave and internal sequence
- DMX 512, 0-10V or potentiometer
- RDM, Ethernet and Wi-Fi with external Remoto accessory

SPECIFICATIONS:

- Max output Voltage @ full power: 42Vdc
- Max output Current @ full power: 500mA/700mA/1000mA
- Channels: 2 parallelable channels
- Max power: 40W @ 230 Vac
- Regulation type: Current / PWM
- Frequency: 600 Hz - 4 KHz , adjustable in 8 steps
- Flicker Free
- Over Temperature Protection
- Power Limit Protection
- Output Short-Circuit Protection
- Ambient Temperature: -25°C - +45°C
- Ambient Umidity: 5% - 90%

PHYSICAL SIZE:

- Dimensions: 158x36x54 cm
- Weight: 230 g
- Attached drawings

CONTROL PROTOCOL AND PROGRAMMING:

- Master-Slave Mode
- USITT Dmx 512/1990
- Dmx Channels: 2 / 3
- RDM
- Input 0/10 V
- Input potentiometer
- Remoto Optional Ready

AVAILABLE COLORS:

- White

ELECTRICAL SPECIFICATIONS/ CONNECTIONS:

- AC power: 100-240 Vac (+/-10%)
- Frequency: 47-63 Hz
- Power Factor: >0,93@230Vac
- Power Consumption: 47 W @ 230 Vac 50 Hz 25°C
- Power connection: AWG 22-12, Terminal Block p.7,5 mm
- External Input: AWG 30-16, Terminal Block p.2,54 mm
- DMX connection: AWG 30-16, Terminal Block p.2,54 mm
- Led connection: AWG 30-16, Terminal Block p.2,54 mm

ACCESSORIES:

- Remoto
- Dmx Opto Hub
- Accessories can be included in special offer



158