

CLASSE LS 40



MAIN VERSIONS

ALL IN 1 FIXTURE

KEY FEATURES

- LED spot moving head ideal for basic application
- As bright as majority of the lamp based 150 spots
- 12.5° beam angle
- Throw distance: 2-7.5 m

LIGHT SOURCE:

- Power engine: 40W COB LED
- CT: 6500°K
- Average led life: 50.000 Hours

SPECIFICATIONS:

Movement

- Pan: 540°/630° optional (16 bit)
- Tilt: 265° (16 bit)
- Advanced moving system: fast, stable and quiet
- X-Y repositioning

Color

- Color wheel: 8 dichroic filters + open, indexable, rainbow effect

Gobo

- 1 Rotating gobo wheel: 7 interchangeable, indexable gobos + open
- Gobo shaking

Prism

- 3 facets, 5 facets, 3D

Focus

- Manual focus

Frost

- Frost filter

Strobe/Black-out/Dimmer

- Strobe: variable, random, pulse effects
- Movement and wheel changing with black-out
- Dimmer: 0-100%

Cooling

- Forced ventilation
- Controlled fan speed
- Temperature info

Mounting

- Quick lock

PHYSICAL SIZE:

- Attached drawings
- Weight: 9 kg
- Packing dimension: 41x31.5x53 cm
- Gross weight: 11 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- 3 Control channel modes: 10/12/14 channels
- 4 operational modes: DMX-512, Slave, Auto, Audio
- LED display, auto lock
- Hibernation
- Show editor
- Diagnostic system
- Software upgrade through DMX

AVAILABLE COLORS:


- Black
- Other on request

ELECTRICAL SPECIFICATION/ CONNECTIONS:


- AC input: 100-240V, 50/60HZ
- Max power consumption: 100 W
- ON/OFF power switch
- Power connection: Schuko power wiring attached
- Dmx connection: 5 poles IN/OUT

ACCESSORIES:

- Dmx cable
- Safety cord
- C clamp
- Updater box
- Flight case
- Accessories can be included in special offer



316



386

222