

CLASSE LS 60



1E300299

KEY FEATURES

- LED spot moving head designed for basic application
- As bright as majority of the well known lamp based 250 spots
- 18° beam angle
- Throw distance: 3-10 m
- Remote Focus

LIGHT SOURCE:

- Power: 80W COB LED
- CT: 6500°K
- Average led life: 50.000 Hours

SPECIFICATIONS:

Movement

- Pan: 540°/630°optional (16 bit)
- Tilt: 265° (16 bit)
- Advanced moving system: fast, stable and quiet
- X-Y repositioning

Color

- Color wheel: 8 dichroic filters + open, indexable, rainbow effect

Gobo

- 1 Rotating gobo wheel: 7 interchangeable, indexable gobos + open
- Gobo shaking

Prism

- 3 facets, 3D

Focus

- Motorized focus

Frost

- Frost filter

Strobe/Black-out/Dimmer

- Strobe: variable, random, pulse effects
- Movement and wheel changing with black-out
- Dimmer: 0-100%

Cooling

- Forced ventilation
- Controlled fan speed
- Temperature info

Mounting

- Quick lock

PHYSICAL SIZE:

- Attached drawings
- Weight: 11 kg
- Packing dimension: 47x33x39 cm
- Gross weight: 13 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- Wireless ready
- 3 Control channel modes: 12/14/16 channels
- 4 operational modes: DMX-512, Slave, Auto, Audio
- LED display, auto lock
- Display settings via battery ready
- Hibernation
- Show editor
- Diagnostic system
- Software upgrade through DMX

AVAILABLE COLORS:


- Black
- Other on request

ELECTRICAL SPECIFICATION/ CONNECTIONS:


- AC input: 100-240V, 50/60HZ
- Max power consumption: 140 W
- ON/OFF power switch
- Power connection: Schuko power wiring attached
- Dmx connection: 3-5 poles IN/OUT

ACCESSORIES:

- Dmx cable
- Safety cord
- C clamp
- Display battery
- Updater box
- Wireless
- Flight case
- Accessories can be included in special offer



316



406

222