



1E200399

KEY FEATURES

- Powerful RGBW LED based wash zoom moving head
- Effect engine for individual led ring control
- Designed for medium/long distance installation
- As bright as majority of the lamp based 700 wash
- 9/43° zoom
- Throw distance: 3-20 m

LIGHT SOURCE:

- 19x15W RGBW Osram leds
- Average led life: 50.000 Hours

SPECIFICATIONS:

Movement

- Pan: 540°/630°optional (16 bit)
- Tilt: 265° (16 bit)
- Advanced motor moving system: fast, stable and quiet
- X-Y repositioning

Color

- RGBW color mixing
- Control of separate rings
- Preset white color temperature steps
- Editable and storable new color temperatures

Zoom

- 9/43°

Strobe/Black-out/Dimmer

- Strobe: variable, random, pulse effects
- Movement with black-out
- Dimmer: Linear digital 0-100%

Cooling

- Heat pipe combined with forced ventilation
- Controlled fan speed
- Temperature info

Mounting

- Any position
- Quick lock

PHYSICAL SIZE:

- Attached drawings
- Weight: 14 kg
- Packing dimension: 58x49x33 cm
- Gross weight: 17 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- RDM ready
- Wireless ready
- 3 Control channel modes: 20/32/42 channels
- 4 operational modes: DMX-512, Slave, Auto, Audio
- Full color LCD graphic display, auto lock
- Display settings via battery ready
- Hibernation
- Show editor
- Diagnostic system
- Software upgrade through DMX

AVAILABLE COLORS:

- Black
- Other on request


ELECTRICAL SPECIFICATION/ CONNECTIONS:

- AC input: 100-240V, 50/60HZ
- Max power consumption: 360 W
- ON/OFF power switch
- Power connection: Powercon IN
- Dmx connection: 3-5 poles IN/OUT


ACCESSORIES:

- Powercon-Schuko power cord
- Dmx cable
- Safety cord
- C clamp
- Display battery
- Updater box
- Wireless
- Flight case

- Accessories can be included in special offer



403



502

234