



**1E701299**

## KEY FEATURES

- Individual pixel control high power LED based bar
- Throw distance: 3-7.5 m
- Versatile
- Light, bright and compact
- Silent

## LIGHT SOURCE:

- Power: 4 X 30 W RGB COB LED
- Average led life: 50.000 Hours

## SPECIFICATIONS:

### Color

- RGB color mixing

### Pixel control

- Individual

### Beam angle

- 60°
- 15° optional assembly

### Strobe/Dimmer

- Strobe: variable
- Dimmer: Linear digital 0-100%

### Cooling

- Forced ventilation
- Controlled fan speed

### Mounting

- Any position
- Adjustable mounting bracket

## PHYSICAL SIZE:

- Attached drawings
- Weight: 4 Kg
- Packing dimension: 53x21x26 cm
- Gross weight: 5 kg

## CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- 4 Control channel modes: 3/5/12/15 channels
- 4 buttons control panel
- LCD display, auto lock
- Preset programs with adjustable flash and speed

## AVAILABLE COLORS:

- Black
- Architectural gray
- Other on request


## ELECTRICAL SPECIFICATION/ CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 120 W
- Power connection: Powercon IN/OUT
- Dmx connection: 3-5 poles IN/OUT

## ACCESSORIES:


- Powercon-Schuko power cord
- Dmx cable
- Safety cord
- 15° parabola assembly
- Flight case

- Accessories can be included in special offer



440

154



137