

PIXEL PAR PIXEL



MAIN VERSIONS

RGB

KEY FEATURES

- RGB COB LED
- Throw distance: 3-10 m
- Versatile
- Wide and narrow beam angle included

LIGHT SOURCE:

- Power engine: 100W RGB COB LED
- Average led life: 50.000 Hours

SPECIFICATIONS:

Color

- RGB color mixing

Beam angle

- 60°
- 30° optional lens

Strobe/Dimmer

- Strobe: variable
- Dimmer: Linear digital 0-100%

Cooling

- Forced ventilation
- Controlled fan speed

Mounting

- Any position
- Adjustable mounting bracket

PHYSICAL SIZE:

- Attached drawings
- Weight: 4.5 kg
- Packing dimension: 28x28x40 cm
- Gross weight: 5.5 kg

CONTROL PROTOCOL

AND PROGRAMMING:

- USITT Dmx 512/1990
- 2 Control channel modes:
 - 3/5 channels
- 4 buttons control panel
- LCD display, auto lock
- Preset programs with adjustable flash and speed

AVAILABLE COLORS:

- Black
- Architectural gray
- Other on request


ELECTRICAL SPECIFICATION/ CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 120 W
- Power connection: Schuko power wiring attached
- Dmx connection: 3 poles IN/OUT


ACCESSORIES:

- Dmx cable
- Safety cord
- 30° lens
- Barndoor
- Flight case

- Accessories can be included in special offer



300



235