

QUADRO SPOT IP65



KEY FEATURES

- RGB COB LED, designed for flood diffusion
- Throw distance: 2,5-8 m
- IP65, for outdoor use
- Silent, no fan
- Die-cast aluminum structure
- Compact size and light weight
- Barndoor option

LIGHT SOURCE:

- Power: 150W RGB COB LED
- Average led life: 50.000 Hours

SPECIFICATIONS:

Color

- RGB color mixing

Beam angle

- 60°

Strobe/Dimmer

- Strobe: variable
- Dimmer: Linear digital 0-100%

Mounting

- Adjustable mounting bracket
- Outdoor: IP65 protection

PHYSICAL SIZE:

- Attached drawings
- Weight: 8 Kg
- Packing dimension: 38x28x42 cm
- Gross weight: 10 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- 3 Control channel modes:
 - 3/5/6 channels
- 4 buttons control panel
- LCD display, key lock
- Preset programs with adjustable flash and speed
- IR remote control ready

AVAILABLE COLORS:

- Black
- Architectural gray
- Other on request

ELECTRICAL SPECIFICATION/ CONNECTIONS:


- AC power: 100-240V, 50/60HZ
- Max power consumption: 160 W
- Power connection: in/out IP65 power wiring attached
- Dmx connection: in/out IP65 data wiring attached

ACCESSORIES:


- Cable adapters
- Safety cord
- Barndoor
- IR remote control
- Flight case

- Accessories can be included in special offer

1E701699



344



326

220