



**1E701699**

### KEY FEATURES

- Individual pixel control, LED based bar
- Versatile for basic application
- Throw distance: 3-8 m
- Mini size for mini spaces
- Silent

### LIGHT SOURCE:

- Power: 16 X 3W RGB LED
- Average led life: 50.000 Hours

### SPECIFICATIONS:

- Color**
  - RGB color mixing
- Pixel control**
  - Individual
- Beam angle**
  - 25°
- Strobe/Dimmer**
  - Strobe: variable
  - Dimmer: Linear digital 0-100%
- Cooling**
  - Forced ventilation
  - Controlled fan speed
- Mounting**
  - Any position
  - Adjustable mounting brackets

### PHYSICAL SIZE:

- Attached drawings
- Weight: 6 Kg
- Packing dimension: 1030x1080x165 cm
- Gross weight: 8 kg

### CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- 6 Control channel modes: 3/5/6/12/24/48 channels
- 4 buttons control panel
- LCD display, auto lock

### AVAILABLE COLORS:


- Black
- Architectural gray
- Other on request

### ELECTRICAL SPECIFICATION/ CONNECTIONS:


- AC power: 100-240V, 50/60HZ
- Max power consumption: 60 W
- ON/OFF power switch
- Power connection: VDE IN
- Dmx connection: 3 poles IN/OUT

### ACCESSORIES:

- VDE-Schuko power cord
- Dmx cable
- Safety cord
- Accessories can be included in special offer



970



65

140