



MAIN VERSIONS

RGBW
12°
24°
38°

KEY FEATURES

- RGBW LED architectural projector, designed to wash
- Throw distance: 4-25 m
- Versatile 12°/24°/38° beam angles
- IP65, for outdoor use
- Die-cast aluminum body

LIGHT SOURCE:

- Power engine: 9 X 30W RGBW LED
- Average led life: 50.000 Hours

SPECIFICATIONS:

Color

- RGBW color mixing
- Preset white color temperature steps
- Linear color temperature adjust

Beam angle

- 12°
- 24°
- 38°

Strobe/Dimmer

- Strobe: variable, random, pulse effects
- Dimmer: Linear digital 0-100% 16 bit resolution
- Flicker free, adjustable PWM frequency

Cooling

- Overheat protected

Mounting

- Adjustable mounting bracket
- Outdoor: IP65 protection

PHYSICAL SIZE:

- Weight: 13 kg
- Packing dimension: 56x46x21 cm
- Gross weight: 14 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- RDM ready
- Bidirectional communication ready
- 2 Control channel modes: 4/8 channels
- 3 operational modes: DMX-512, Slave, Auto
- LED display for settings, key lock
- Remote display functions
- Software upgrade through remote controller

AVAILABLE COLORS:

- Black
- Architectural gray
- Other on request


ELECTRICAL SPECIFICATION/ CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 270 W
- Power connection: free wire
- Dmx connection: free wire


ACCESSORIES:

- Free wire
- Optional parabola assembly
- Remote data information device
- Safety cord

- Accessories can be included in special offer



405



507