

CLASSE **S 15R** RS



MAIN VERSIONS


ALL IN 1 FIXTURE

KEY FEATURES

- Lamp based spot moving head fully equipped
- 6° - 28° Linear zoom
- CMY
- Effect engine
- Flicker free
- Throw distance: 5-25 m


LIGHT SOURCE:

- Philips Platinum 15R
- Power engine: 300W
- CT: 8000° K
- Average led life: 1500 Hours



391

419



559

331

SPECIFICATIONS:

Movement

- Pan: 540° - 630° optional (16 bit)
- Tilt: 270° (16 bit)
- Advanced moving system: fast, stable and quiet
- X-Y repositioning

Color

- CMY module (16bit)
- Color wheel: 6 dichroic filters, indexable, rainbow effect
- CTO

Gobo

- 1 Rotating wheel: 8 interchangeable, indexable gobos
- 1 Static wheel: 14 gobos
- Gobo shaking

Prism

- Rotating prism: 3 facets

Focus & Zoom

- Motorized linear focus
- Zoom: 6° - 28° linear zoom

Frost

- Frost 0-100%

Iris

- Motorized linear iris 5% to 100%

Strobe/Black-out/Dimmer

- Strobe: variable, random, pulse effects
- Movement and wheel changing with black-out
- Dimmer: Linear 0-100%

Cooling

- Forced ventilation
- Controlled fan speed
- Temperature info

Mounting

- Any position
- Quick lock

PHYSICAL SIZE:

- Attached drawings
- Weight: 22.5 kg
- Packing dimension: 76.5x50.5x46.5 cm
- Gross weight: 26.5 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- RDM ready
- Wireless ready
- 3 Control channel modes: 21/23/34 channels
- 4 operational modes: DMX-512, Slave, Auto, Audio
- LCD color display, auto lock
- Display settings via battery ready
- Hibernation
- Show editor
- Diagnostic system
- Software upgrade through DMX

AVAILABLE COLORS:

- Black
- Other on request

ELECTRICAL SPECIFICATIONS/ CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 500 W
- Power connection: Powercon IN/OUT
- Dmx connection: 3-5 poles IN/OUT

ACCESSORIES:

- Dmx cable
- Safety cord
- C clamp
- Display battery
- Updater box
- Wireless
- Flight case

- Accessories can be included in special offer