




1E100099

KEY FEATURES


- Lamp based beam/acl moving head fully equipped
- 6° beam angle
- CMY module
- Effect engine
- Flicker free
- Solid structure, road proof
- Throw distance: 10-50 m

LIGHT SOURCE:

- Philips MSR GOLD 700/2 MiniFastFit
- Power: 700W
- CT: 7200° K
- Average led life: 750 Hours



488



467

564

SPECIFICATIONS:

Movement

- Pan: 540°/630°optional (16 bit)
- Tilt: 265°(16 bit)
- Advanced moving system: fast, stable and quiet
- X-Y repositioning

Color

- CMY quick in-out module
- Color wheel: 7 dichroic filters + open, indexable, rainbow effect
- Linear CTO

Beam angle

- 6°

Gobo

- Quick in-out module
- 1 Static gobo wheel: 7 interchangeable gobos + open
- 1 Rotating gobo wheel: 6 interchangeable indexable gobos + open
- Gobo shaking

Prism

- Rotating prism: 3 facets

Focus

- Motorized linear focus

Frost

- Linear frost

Strobe/Black-out/Dimmer

- Strobe: variable, random, pulse effects
- Movement and wheel changing with black-out
- Dimmer: Linear 0-100%

Cooling

- Forced ventilation
- Controlled fan speed
- Temperature info

Mounting

- Any position
- Quick lock

PHYSICAL SIZE:

- Attached drawings
- Weight: 34 kg
- Packing dimension: 59x48x80 cm
- Gross weight: 36 kg

CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- RDM ready
- Wireless ready
- 3 Control channel modes: 19/21/32 channels
- 4 operational modes: DMX-512, Slave, Auto, Audio
- LCD color display, auto lock
- Display settings via battery ready
- Hibernation
- Show editor
- Diagnostic system
- Software upgrade through DMX

AVAILABLE COLORS:

- Black
- Other on request

ELECTRICAL SPECIFICATION/

CONNECTIONS:

- AC power: 100-240V, 50/60HZ
- Max power consumption: 1000 W
- Power connection: Schuko power wiring attached
- Dmx connection: 3-5 poles IN/OUT

ACCESSORIES:

- Dmx cable
- Safety cord
- C clamp
- Display battery
- Updater box
- Wireless
- Flight case
- Accessories can be included in special offer