



## MAIN VERSIONS

### ALL IN 1 FIXTURE

## KEY FEATURES

- Bright beam moving head
- Effect engine
- Focus, rotating gobos and prism
- 3° beam angle
- Throw distance: 5-50 m

## LIGHT SOURCE:

- Philips Platinum 5R
- Power engine: 189W
- CT: 7100° K
- Average led life: 2000 Hours

## SPECIFICATIONS:

### Movement

- Pan: 540°/630° optional (16 bit)
- Tilt: 270° (16 bit)
- Advanced 3 phases motor moving system: fast, stable and quiet
- X-Y repositioning

### Color

- Color wheel: 12 dichroic filters
- +open, indexable, rainbow effect

### Beam angle

- 3°

### Gobo

- 1 Rotating gobo wheel: 8 interchangeable, indexable gobos
- Gobo shaking

### Prism

- Rotating prism: 8 facets

### Focus

- Motorized linear focus

### Strobe/Black-out/Dimmer

- Strobe: variable, random, pulse effects
- Movement and wheel changing with black-out
- Dimmer: Linear digital 0-100%

### Cooling

- Forced ventilation
- Controlled fan speed
- Temperature info

### Mounting

- Any position
- Quick lock

## PHYSICAL SIZE:

- Weight: 16 kg
- Packing dimension: 63x46x46 cm
- Gross weight: 19 kg

## CONTROL PROTOCOL AND PROGRAMMING:

- USITT Dmx 512/1990
- Wireless ready
- Remote functions ready
- RDM functions ready
- 3 Control channel modes: 12/14/18 channels
- 4 operational modes: DMX-512, Slave, Auto, Audio
- LCD color display, auto lock
- Display settings via battery ready
- Hibernation
- Show editor
- Diagnostic system
- Software upgrade through DMX

## AVAILABLE COLORS:


- Black
- Other on request

## ELECTRICAL SPECIFICATIONS/ CONNECTIONS:


- AC power: 100-240V, 50/60HZ
- Max power consumption: 350 W
- ON/OFF power switch
- Power connection: Powercon IN
- Dmx connection: 3-5 poles IN/OUT

## ACCESSORIES:

- Powercon-Schuko power cord
- Dmx cable
- Safety cord
- C clamp
- Display battery
- Updater box
- Wireless
- Flight case
- Accessories can be included in special offer



339



498

331